Safety data sheet


according to 1907/2006/EC, Article 31

Printing date 26.06.2015

ouilding gualit

Version number 1

Revision: 04.06.2015



Printing date 26.06.2015

soma

building quality

Version number 1

Revision: 04.06.2015


Trade name: ISOMAT AK -22

	(Contd. of page 1)		
• Hazard stateme	nts		
H315 Causes sk	H315 Causes skin irritation.		
H318 Causes se	rious eye damage.		
H317 May caus	e an allergic skin reaction.		
H335 May caus	e respiratory irritation.		
· Precautionary s	statements		
P102	Keep out of reach of children.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if			
	present and easy to do. Continue rinsing.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.		
P501	Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		
· 2.3 Other hazar	rds		
The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or			
formaldehydes.			
· Results of PBT	and vPvB assessment		
• PBT: Not applie			
• vPvB: Not appl	icable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.





· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 26.06.2015

Version number 1

Revision: 04.06.2015

(Contd. of page 2)

Trade name: ISOMAT AK -22

• 5.3 Advice for firefighters

• Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

<u>SECTION 7: Handling and storage</u>

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

• *Additional information:* The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

GB



Printing date 26.06.2015

 \mathbf{O}

building quality

Version number 1

Revision: 04.06.2015

Trade name: ISOMAT AK -22

(Contd. of page 3) Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

Appearance:	G 1: 1	
Form:	Solid	
Colour: Odour:	According to product specification	
Odour: Odour threshold:	Characteristic Not determined.	
pH-value:	Not applicable.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not applicable.	
Density at 20 °C:	1.5 g/cm ³	
Relative density	Not determined.	
Vapour density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Soluble.	

GB

Printing date 26.06.2015

Version number 1

Revision: 04.06.2015

(Contd. of page 4)

Trade name: ISOMAT AK -22

• **Partition coefficient (n-octanol/water):** Not determined.

- Viscosity:
- Dynamic:
- Kinematic:
- 9.2 Other information

Not applicable. Not applicable. No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitisation: Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 6)



Printing date 26.06.2015

soma

building quality

Version number 1

Revision: 04.06.2015

Trade name: ISOMAT AK -22

(Contd. of page 5)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport informat	tion	
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
 14.5 Environmental hazards: Marine pollutant: 	No	
· 14.6 Special precautions for user	Not applicable.	
• 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	-	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:
- Cement, portland
- · Hazard statements
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.

· Precautionary statements

- P102 Keep out of reach of children.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- *P280 Wear protective gloves/protective clothing/eye protection/face protection.*
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 7)

^{- ,)} — GB

GR

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2015

building quality

Version number 1

Revision: 04.06.2015

Trade name: ISOMAT AK -22

	(Contd. of page 6)
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

· Department issuing MSDS: Product safety department.

· Contact:

Mrs. Demirtzoglou

Mrs. Papageorgiou

• Abbreviations and acronyms: Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3