Printing date 18.11.2015

building qualit

Version number 1

Revision: 20.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: EPOMAX L-20 (B) 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Epoxy curing agent \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: ISOMAT S.A. **Building Chemicals & Mortars** 17th km Thessaloniki-Ag. Athanasios GR-57003 Ag. Athanasios Greece • Further information obtainable from: purchase@isomat.gr • 1.4 Emergency telephone number: +30 2310 576 000 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation EC No 1272/2008 GHS05 corrosion Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin. Skin Sens. 1 H317 May cause an allergic skin reaction. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS05, GHS07 · Signal word Danger · Hazard-determining components of labelling: 2,2'-iminodiethylamine Benzyl alcohol · Hazard statements H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eve damage. H317 May cause an allergic skin reaction. · Precautionary statements P102 Keep out of reach of children. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. Immediately call a POISON CENTER/doctor. P310 P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 2) GB

Printing date 18.11.2015

building quality

Version number 1

Revision: 20.02.2015

(Contd. of page 1)

Trade name: EPOMAX L-20 (B)

· 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

· Results of PBT and vPvB assessment

- *PBT:* Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 111-40-0	2,2'-iminodiethylamine	25-50%
EINECS: 203-865-4	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4,	
Index number: 612-058-00-X	H312; Skin Sens. 1, H317	
CAS: 100-51-6	Benzyl alcohol	25-50%
EINECS: 202-859-9	() Acute Tox. 4, H302; Acute Tox. 4, H332	
Index number: 603-057-00-5		
. Additional information · For	the wording of the listed risk phrases refer to section 16	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:
- Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

GB

Printing date 18.11.2015

 \mathbf{om}

ouilding gualit

Version number 1

Revision: 20.02.2015

Trade name: EPOMAX L-20 (B)

(Contd. of page 2)
6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. • Information about fire - and explosion protection: No special measures required.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-40-0 2,2'-iminodiethylamine

WEL Long-term value: 4.3 mg/m³, 1 ppm Sk

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

GB

Version number 1

Revision: 20.02.2015

Trade name: EPOMAX L-20 (B)

· Material of gloves

Printing date 18.11.2015

soma

building quality

(Contd. of page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information		
Appearance:		
Form:	Fluid	
Colour:	Light yellow	
Odour:	Ammonia-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	l g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic at 20 °C:	48 mPas	
Kinematic:	Not determined.	

building quality

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.11.2015

Version number 1

Revision: 20.02.2015

(Contd. of page 4)

Trade name: EPOMAX L-20 (B)

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

111-40-0 2,2'-iminodiethylamine

LD50 1080 mg/kg (rat) Oral

Dermal LD50 1090 mg/kg (rabbit)

100-51-6 Benzyl alcohol

LD50 1230 mg/kg (rat) Oral

Dermal LD50 2000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation Caustic effect on skin and mucous membranes.

· Serious eve damage/irritation Strong caustic effect.

· Respiratory or skin sensitisation Sensitisation possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 6)

GB

Printing date 18.11.2015

Version number 1

Revision: 20.02.2015

Trade name: EPOMAX L-20 (B)

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	UN3267
ADR, IMDG, IATA	0113207
14.2 UN proper shipping name	
ADR	3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O (DIETHYLENETRIAMINE)
IMDG, IATA	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.
	(DIETHYLENETRIAMINE)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
<u>uir 220</u>	
Class	8 Corrosive substances.
Label	8
14.4 Packing group	
ADR, IMDĞ, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80 5 4 6 D
EMS Number:	F-A,S-B
Segregation groups	Alkalis
14.7 Transport in bulk according to Ann	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	Ĕ



(Contd. of page 5)

Printing date 18.11.2015

building quality

Version number 1

Revision: 20.02.2015

Trade name: EPOMAX L-20 (B)

	(Contd. of page 6)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (DIETHYLENETRIAMINE), 8, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS05, GHS07 · Signal word Danger · Hazard-determining components of labelling: 2,2'-iminodiethylamine Benzyl alcohol · Hazard statements H302+H312 Harmful if swallowed or in contact with skin. *H314* Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. · Precautionary statements P102 Keep out of reach of children. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P310 Immediately call a POISON CENTER/doctor. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H332 Harmful if inhaled.

· Department issuing MSDS: Product safety department.

· Contact:

Mrs. Demirtzoglou

Mrs. Papageorgiou

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 8)

GB



Revision: 20.02.2015

(Contd. of page 7)

GB

Printing date 18.11.2015

Version number 1

Trade name: EPOMAX L-20 (B)

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1